Siesta-TA Digital Thermostat




Technical Characteristics

- Heating and Cooling
- 2-wire digital thermostat
- Ideal for use in grid or 3-wire motorized valve (recommended by major manufacturers)
- Turn on and run
- 2-button keypad for easy and intuitive programming
- Function On / Off / antifreeze (5 to 18 °C). In Off the antifreeze function is active, it is as simple as pressing the two keys simultaneously △ + ☑ = ②
- 2 setpoints: Comfort and Economy
- Contact status indication on display heating (a), cooling (b), antifreeze
- Heating or cooling selection by key (no need to enter programming)
- Internal temperature sensor with adjustment scale 5 to 35 ° C
- Temperature in °C (Celsius) or in °F (Fahrenheit)
- Adjustable differential on heating from 0,1 to 2 °K, on cooling of 0,2 to 2 °K
- Lock adjustment scale, by maximum and minimum selectable
- Probe calibration
- Powered by 2 batteries x 1.5V AAA, alkaline
- Maintains program in memory even without batteries
- Potential free changeover relay 8 Amps
- Dimensions 100 x 80 x 20 mm, suitable for universal box
- Relay action selectable from all/nothing or time modulating
- ErP class IV (2%)
- Ecodesign Compliant EU2015/1188

Wiring diagram

note: Calefacción= Heating, Refrigeración= Cooling



Model	Code	Description
Siesta-TA	29.000	Digital Thermostat

All rights reserved and contents of this document. Forbidden any reproduction in whole or part of this publication in any form without prior written permission from SONDER REGULACION S.A. The graphics and information herein are approximate and may include technical inaccuracies or typographical errors. SONDER REGULACION, S.A. reserves the right to modify this document without notice. Performance, design and typesetting: SONDER REGULACION,

