

Siesta 105 WiFi 3C



Control the comfort of your home from your mobile
All/nothing output 3 contacts, programmable, e-ink



Digital thermostat for heating and/or cooling, programmable, wall mounting, wire communication, relay output (3 contacts), large low power electronic ink display, WiFi programming. Keyboard lock from the app. Ideal for tourist apartments.


Technical features

- Dimensions: Wired transmitter wire 105 x 105 x 25 mm, wired receiver wire 76 x 76 x 30 mm
- Power supply at 230Vac
- Internal temperature and humidity sensor
- Regulation range 5 to 35°C, reading range 0°C to 50°C
- Distance between the thermostat and the boiler link: 75 meters
- Compatible with : WiFi 802.11b/g/r (**2.4GHz**)
- WiFi security support: Open/WEP/WFA/WPA2-personal (TKIP and AES)
- From the thermostat itself you can select room temperature, stop or start
- 3 tactile buttons
- When stopped, it changes to the anti-frost setpoint, this is a configurable value
- Using free apps, IOS and Android compatible, installed on your smartphone, you will be able to configure:
 - Comfort schedules, economy, unemployment, anti-frost
 - Heating or cooling control mode. In heating mode it controls by temperature, relative humidity only senses it. **In cooling mode it controls by both temperature and humidity.**
 - Calibration between displayed and sensed temperature
 - Maximum temperature and minimum temperature set point range
 - **Keyboard lock for tampering, ideal for tourist apartments**
 - Adjustable tripping differential (0.1 to 3°K)
 - Temperature and humidity statistics
 - Stop (switch to anti-freeze) / ON
- Outputs: 1 changeover relay (SPDT, 5Amp resistive, potential-free contacts)
- Local communication via WiFi for programming or consultation from smartphone
- For new homes, unoccupied and without WiFi, it works manually (test for the installer).
- Electronic ink display:
 - Display of relay status (on/off) in heating or air conditioning mode e.g. motorized grille
 - Temperature in °C (Celsius)
 - Relative humidity of the environment


- It keeps the programming in memory, because it is in the app.
- The plate to fix the receiver to a 60 mm diameter box is an optional accessory, code 3.970 (Placa TA)
- Equipped with a reset button.

Wiring diagram for relay:


Rejilla motorizada alimentada a 230V~




Válvula zona alimentada a 230V~ a 3 hilos



Termostato




Enlace caldera



Opcional Código: 3.970

Placa TA (placa montaje + tornillos)



Model	Code	Description	Price (without VAT)
Siesta 105 WiFi 3C	29.104	Digital wired thermostat, programmable, switched SPDT relay ONLY. WiFi Communication. 2nd Generation	.- €

All rights and contents of this document are reserved. Total or partial reproduction of this publication by any means is prohibited without prior written authorisation from SONDER REGULACIÓN S.A. The graphics and information described in this document are for guidance only and may include technical or typographical errors. SONDER REGULACIÓN S.A. reserves the right to modify this document without prior notice. Production, design and photocomposition: SONDER REGULACIÓN S.A.